



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** NANTEN SL BIO EPOKSIPINNOITE B-OSA
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Hardener for concrete coatings. For professional use only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** Nanten Oy
Teollisuustie 6
04300 Tuusula - Finland
Phone.: +358 9 2747970
nanten@nanten.com
www.nanten.com
- 1.4 Emergency telephone number:** Emergency telephone number Europe: 112

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:**CLP Regulation (EC) n° 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.

Acute Tox. 4: Acute toxicity, Category 4, H302+H332

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1B: Skin corrosion, Category 1B, H314

Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

2.2 Label elements:**CLP Regulation (EC) n° 1272/2008:**

Danger

**Hazard statements:**

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Sens. 1B: H317 - May cause an allergic skin reaction

Precautionary statements:

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing

P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

Supplementary information:

EUH071: Corrosive to the respiratory tract

Substances that contribute to the classification

Benzyl alcohol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; m-phenylenebis(methylamine); Salicylic acid

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION (continue)

2.3 Other hazards:

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:**Chemical description:** Epoxy hardener based on amines**Components:**

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 100-51-6 EC: 202-859-9 Index: 603-057-00-5 REACH: Non-applicable	Benzyl alcohol ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H302+H332 - Warning	30 - 60 %
CAS: 2855-13-2 EC: 220-666-8 Index: 612-067-00-9 REACH: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H302+H312; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	10 - 30 %
CAS: 1477-55-0 EC: 216-032-5 Index: Non-applicable REACH: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) Self-classified Regulation 1272/2008 Acute Tox. 3: H331; Acute Tox. 4: H302; Aquatic Chronic 3: H412; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1B: H317 - Danger	5 - 15 %
CAS: 69-72-7 EC: 200-712-3 Index: Non-applicable REACH: 01-2119486984-17-XXXX	Salicylic acid Self-classified Regulation 1272/2008 Acute Tox. 4: H302+H332; Eye Dam. 1: H318; STOT SE 3: H335 - Danger	1 - 5 %

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as dangerous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of modifications on the skin (stinging, redness, rashes, blisters,...), seek medical advice with this Security Data Sheet

By eye contact:

This product does not contain substances classified as dangerous for eye contact. Rinse eyes thoroughly for at least 15 minutes with lukewarm water, ensuring that the person affected does not rub or close their eyes.

By ingestion/aspiration:

Request immediate medical assistance, showing the SDS of this product. Do not induce vomiting, because its expulsion from the stomach can be hazardous to the mucus of the main digestive tract, and its inhalation, to the respiratory system. Rinse out the mouth and throat, as they may have been affected during ingestion. In the case of loss of consciousness do not administrate anything orally unless supervised by a doctor. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

- CONTINUED ON NEXT PAGE -

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media:**

Product is non-flammable under normal conditions of storage, manipulation and use. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:****A.- Precautions for safe manipulation**

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, manipulation and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:**A.- Technical measures for storage**

Store in a cool, dry, well-ventilated location

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continue)

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no environmental limits for the substances contained in the product



8.2 Exposure controls:

A.- General security and hygiene measures in the work place





As a preventative measure it is recommended to use basic Personal Protection Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.





B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours (AX)		EN 405:2001+A1:2009	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (BU)		EN 420:2003+A1:2009	Replace the gloves at any sign of deterioration.
 Mandatory hand protection	Chemical protective gloves (PVA)		EN 420:2003+A1:2009	Replace the gloves at any sign of deterioration.

D.- Ocular and facial protection





Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face mask		EN 166:2001 EN 167:2001 EN 168:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.
 Mandatory face protection	Panoramic glasses against liquid splash		EN 166:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection



- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2011 EN 13832-1:2006 EN ISO 20344:2011	Replace boots at any sign of deterioration.
 Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 EN 168:2001 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2001 EN ISO 6530:2005 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

Physical state at 20 °C: Liquid
Appearance: Fluid
Color: Yellowish
Odor: Aminic

Volatility:

Boiling point at atmospheric pressure: 180 °C
Vapour pressure at 20 °C: Non-applicable *
Vapour pressure at 50 °C: Non-applicable *
Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: Non-applicable *
Relative density at 20 °C: 1,1
Dynamic viscosity at 20 °C: 100 - 300 mPas
Kinematic viscosity at 20 °C: Non-applicable *
Kinematic viscosity at 40 °C: Non-applicable *
Concentration: Non-applicable *
pH: Non-applicable *
Vapour density at 20 °C: Non-applicable *
Partition coefficient n-octanol/water 20 °C: Non-applicable *
Solubility in water at 20 °C: Non-applicable *
Solubility properties: Non-applicable *
Decomposition temperature: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)

Melting point/freezing point: Non-applicable *

Flammability:

Flash Point: 120 °C

Autoignition temperature: Non-applicable *

Lower flammability limit: Non-applicable *

Upper flammability limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Precaution	Not applicable	Not applicable

10.6 Hazardous decomposition products:See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Corrosive product, its consumption causes burns destroying the full thickness of fabrics. For more information on the secondary effects of contact with the skin see section 2.

B- Inhalation:

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes:

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continue)

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
 - Contact with the eyes: Produces serious eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensibilizing effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT)-time exposure:
- Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- G- Specific target organ toxicity (STOT)-repeated exposure:
- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:
- Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	LD50 oral	1230 mg/kg	Rat
	LD50 dermal	2001 mg/kg	Rabbit
	LC50 inhalation	4178 mg/L (4 h)	Rat
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LD50 oral	500 mg/kg (ATEI)	
	LD50 dermal	1100 mg/kg	
	LC50 inhalation	Non-applicable	
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	LD50 oral	1090 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	3 mg/L (4 h) (ATEI)	
Salicylic acid CAS: 69-72-7 EC: 200-712-3	LD50 oral	891 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (4 h) (ATEI)	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Specie	Genus
3-aminomethyl-3,5,5-trimethylcyclohexylamine CAS: 2855-13-2 EC: 220-666-8	LC50	10 - 100 mg/L (96 h)		Fish
	EC50	10 - 100 mg/L		Crustacean
	EC50	10 - 100 mg/L		Algae
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	LC50	10 - 100 mg/L (96 h)		Fish
	EC50	10 - 100 mg/L (48 h)		Crustacean
	EC50	10 - 100 mg/L (72 h)		Algae

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continue)

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
	Parameter	Value	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	94 %
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	BOD5	Non-applicable	Concentration	14 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	49 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	BCF	0,3
	Pow Log	1,1
	Potential	Low
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	BCF	3
	Pow Log	0,18
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Parameter	Value	Parameter	Value
Benzyl alcohol CAS: 100-51-6 EC: 202-859-9	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	36790 N/m (25 °C)	Moist soil	Non-applicable
m-phenylenebis(methylamine) CAS: 1477-55-0 EC: 216-032-5	Koc	1300	Henry	Non-applicable
	Conclusion	Low	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable
Salicylic acid CAS: 69-72-7 EC: 200-712-3	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	24440 N/m (207,25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	Waste paint and varnish containing organic solvents or other dangerous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP4 Irritant — skin irritation and eye damage, HP6 Acute Toxicity, HP8 Corrosive, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2015 and RID 2015:



- 14.1 UN number:** UN3066
- 14.2 UN proper shipping name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** II
- 14.5 Dangerous for the environment:** No
- 14.6 Special precautions for user**
Special regulations: 163, 367
Tunnel restriction code: E
Physico-Chemical properties: see section 9
Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 37-14:



- 14.1 UN number:** UN3066
- 14.2 UN proper shipping name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** II
- 14.5 Dangerous for the environment:** No
- 14.6 Special precautions for user**
Special regulations: 163, 944
EmS Codes: F-A, S-B
Physico-Chemical properties: see section 9
Limited quantities: 1 L
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2015:



- 14.1 UN number:** UN3066
- 14.2 UN proper shipping name:** PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
- 14.3 Transport hazard class(es):** 8
Labels: 8
- 14.4 Packing group:** II
- 14.5 Dangerous for the environment:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable

Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

Modifications related to the previous security card which concerns the ways of managing risks. :

Non-applicable

Texts of the legislative phrases mentioned in section 2.:

H314: Causes severe skin burns and eye damage

H318: Causes serious eye damage

H317: May cause an allergic skin reaction

H412: Harmful to aquatic life with long lasting effects

H302+H332: Harmful if swallowed or if inhaled

Texts of the legislative phrases mentioned in section 3.:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) n° 1272/2008:

Acute Tox. 3: H331 - Toxic if inhaled

Acute Tox. 4: H302 - Harmful if swallowed

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin

Acute Tox. 4: H302+H332 - Harmful if swallowed or if inhaled

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects

Eye Dam. 1: H318 - Causes serious eye damage

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage

Skin Sens. 1: H317 - May cause an allergic skin reaction

Skin Sens. 1B: H317 - May cause an allergic skin reaction

STOT SE 3: H335 - May cause respiratory irritation

Classification procedure:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continue)

Skin Corr. 1B: Calculation method
Eye Dam. 1: Calculation method
Skin Sens. 1B: Calculation method
Aquatic Chronic 3: Calculation method
Acute Tox. 4: Calculation method

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>
<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -