

## DECLARATION OF PERFORMANCE

**No. EU 305/2011**

**Nanten M Primer  
Nanten HM Epoksi  
Nanten ESD Primer  
Nanten HM ESD**

**No. DOP: HMESD2015 (3)**

1. Unique identification code of the product-type:

**EN 1504-2; ZA.1d and ZA.1f**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number, see packaging of the product**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical inspection, as foreseen by the manufacturer:

**EN 1504-2  
Part 2: Surface protection systems for concrete  
Physical resistance (5.1)**

4. Name, registered trade name of registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Nanten Oy  
Teollisuustie 6  
FI-04300 Tuusula  
FINLAND**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

--

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V.

**System 2+ (for uses in buildings and civil engineering works)**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 1504-2, System 2+**

**The notified body No: 0809 VTT Expert Service Ltd has performed the initial inspection of the manufacturing plant and of factory production control and continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued: Certificate of conformity of the factory production control No. 0809-CPR-1037.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

--

9. Declared performance:

**EN 1504-2**

**Epoxy system**, consisting of components:

**Primers     Nanten HM Epoksi, Nanten M Primer and Nanten ESD Primer**

**Masses     Nanten HM ESD Epoksi**

<b>Essential characteristics</b>	<b>Performance</b>	<b>Harmonized Technical Specification</b>
Abrasion resistance EN ISO 5470-1	< 3 000 mg	EN 1504-2:2004
Capillary absorption and permeability to water EN 1062-2	$W < 0,1 \text{ kg/m}^2 \times \text{h}^{0.5}$	EN 1504-2:2004
Impact resistance EN ISO 6272-1	Class III (best in class) $\geq 20 \text{ Nm}$	EN 1504-2:2004
Adhesion strength by pull-off test: EN 1542	$\geq 1,5 \text{ N/mm}^2$	EN 1504-2:2004
Fire Classification EN 13501-1	B <sub>FL</sub> – s1	EN 1504-2:2004
Electrical conductivity	IEC EN 61340-5-1/2	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration on performance is issued under the sole responsibility of the manufacturer in point 4.

Signed for and on behalf of manufacturer by:

Tuusula 4.3.2015

Kari Holopainen, Head of Research and Development